



MegaFlow 3000

Advanced Polycarboxylated Superplasticiser

DESCRIPTION **MegaFlow 3000** is a high performance concrete superplasticiser based on modified polycarboxylate ether. Having unique carboxylic ether polymer, it is an effective cement dispersant and accelerates initial strength.

STANDARD ASTM C494, Type E; BSEN 934-2

USES **MegaFlow 3000** is used for ready-mix concrete, self compacting concrete, under water concrete, precast concrete, concrete containing silica fume, GGBS, PFA with extremely low w/c ratio, etc. It is useful especially for ultra high strength concrete, high fines concrete, cold weather concrete, etc.

ADVANTAGES

- Produces high flowing concrete without segregation
- High early strength in cold weather condition
- Faster turn around of precast moulds
- Increased durability
- Improved surface finish
- Lower permeability
- Increased flexural strengths

TYPICAL PROPERTIES at 25°C

PROPERTY	TEST METHOD	VALUE
Component	-	Single
Form	-	Liquid
Colour	-	Opaque
Specific Gravity	ASTM C494	1.11 +/- 0.02
Air Entrainment	ASTM C231	Up to 1% over Control mix
Chloride Content	BSEN 480-10	Nil to BSEN 934-2
pH	ASTM C494	5-7

COMPATIBILITY **MegaFlow 3000** can be used with all types of cements and cementitious materials like fly ash, GGBS, micro silica etc. **MegaFlow 3000** should not be premixed with other admixtures.

DOSAGE Recommended dosage is 0.5 - 1.5% by weight of cementitious material. Optimum dosage of **MegaFlow 3000** and effect on concrete properties such as workability, strength, setting time, etc. are best assessed after preliminary tests on site using the actual materials of mixes under consideration. For Self Compacting Concrete, a viscosity enhancer **MegaAdd VE** may be required at a dosage between 0.5 - 2.0 ltrs per cubic meter.



MegaFlow 3000

EFFECT OF OVERDOSING Overdosing may result in higher workability and can affect setting. In such cases, provided the concrete is properly cured, the ultimate strength will generally be higher than the regular concrete.

PACK SIZE 20 ltr, 200 ltr, 1000 ltr and bulk

DISPENSING **MegaFlow 3000** should be dispensed into the concrete mixer together with the mixing water.

GENERAL INFORMATION

Shelf Life	12 months from date of manufacture when stored under warehouse conditions in original unopened packing. Extreme temperature / humidity may reduce shelf life.
Cleaning	Clean all equipment and tools with water immediately after use.

HEALTH and SAFETY

PPE's	Gloves, goggles and suitable mask must be worn.
Precautions	Contact with skin, eyes etc. must be avoided. If swallowed seek medical attention immediately.
Hazard	Regarded as non-hazardous for transportation.
Disposal	Do not reuse containers. To be disposed off as per local rules and regulations.
Additional Information	Refer MSDS. (Available on request)

TECHNICAL SERVICE **CONMIX Technical Services** are available on request for onsite support to assist in the correct use of its products.



Construction Solutions for Africa

CAPE TOWN

Tel: +27 (0)87 231 0253
Unit 5 | M5 Freeway Park
Upper Camp Rd | Maitland | 7405
Cape Town | South Africa

JOHANNESBURG

Tel: +27 (0)82 785 8529
64 Maple Street | Pomona
Kempton Park | Johannesburg | 1619
South Africa

Email: info@msasa.co.za | www.msasa.co.za

Manufacturer:

CONMIX LTD.

P.O. Box 5936, Sharjah
United Arab Emirates
Tel: +971 6 5314155
Fax: +971 6 5314332
Email: conmix@conmix.com

Sales Office:
Tel: +971 6 5682422
Fax: +971 6 5681442
www.conmix.com



It is the customer's responsibility to satisfy themselves by checking with the company whether information is still current at the time of use. The customer must be satisfied that the product is suitable for the use intended. All products comply with the properties shown on current data sheets. However, Conmix does not warrant or guarantee the installation of the products as it does not have any control over installation or end use of the product. All information and particularly the recommendations relating to application and end use are given in good faith. The products are guaranteed against any manufacturing defects and are sold subject to Conmix standard terms and conditions of sale.